

11 Office & Kitchen > LED Linear Profiles Medium size

**38151A/W/W**



50W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with 1250mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Accessories



050170



050170C/B

Related items





38150E/B

Physical Specification

|                   |                                 |
|-------------------|---------------------------------|
| Item Group        | 11 Office & Kitchen             |
| Family            | LED Linear Profiles Medium size |
| Order Code        | 38151A/W/W                      |
| Colour            | White                           |
| Material          | Aluminium                       |
| Shape             | Rectangular                     |
| Length            | 1500mm                          |
| Width             | 70mm                            |
| Height            | 35mm                            |
| Surface Ceiling   | Yes                             |
| Suspended Ceiling | Yes                             |
| Indoor            | Yes                             |
| Adjustable        | No                              |

Electrical Characteristics

|                  |   |
|------------------|---|
| Gear             | Built In  |
| Fitting + Driver |   |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Safety Class     |  |
| Power(Watts)     | 50W   |
| IP Rating        | IP20  |

|              |   |
|--------------|---|
| Light Source | LED built in  |
| Dimmable     | No  |
| Cable Length | 300cm   |
| F Mark       |  |


#### Fitting

|               |                  |
|---------------|------------------|
| Input Type    | Constant Current |
| Input Current | 1250mA           |
| Voltage       | 37V              |
| Power(Watts)  | 46,25W           |
| IP Rating     | IP20             |
| Light Source  | LED built in     |
| LED Type      | SMD 2835         |
| LED Brand     | Epistar          |

#### Gear

|                  |   |
|------------------|---|
| Gear Type        | Led Driver  |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Power(Watts)     | 35-50W  |
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 1250mA           | 28-40V  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Brand            | BOKE  |
| Protection       | 0   |

#### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 3000K   |
| Lumen Output         | 4250lm  |
| Light Efficiency     | 85lm/W  |
| CRI                  | 90  |
| Beam Angle           | 120°  |
| Illumination Diagram |  |
| UGR                  | 19  |

#### Packing Info

|            |               |
|------------|---------------|
| Box Weight | 2.420kg       |
| Pcs/Carton | 9             |
| Barcode    | 5291889070245 |
| HS Code    | 9405413990    |

#### Certification & Warranty

|          |         |
|----------|---------|
| Warranty | 3 years |
|----------|---------|

switch to  
**one light!**

one  
LIGHT

